Pneumatic Forklifts

Pneumatic lift trucks are generally known as pallet trucks or pump trucks and are widely utilized in warehouses and shipping plants to transfer materials on pallets. Pneumatic jacks consist of a pair of metallic forks installed on a wheeled counterweight that has a pump. The pump is used to raise and lower the forks.

Visually check the pallet vehicle prior to loading. Make sure the wheels are free of any would-be obstructions. Moreover, make sure the handle moves easily and turns appropriately. Inspect the pallet prior to moving it to assess if it is stacked in a way that minimizes the possibility of anything falling off during lifting. Release any air in the pump and lower the forks to the ground by squeezing the handle installed on the inside of the metal loop on the end of the handle. Run the blades into the slots in the pallet and ensure the blades are centered so that the palletsâ?? mass is evenly dispersed.

Pump the pneumatic lift handle up and down to elevate the forks from the ground. Stop pumping when the pallet is fully off the floor as there is no need to lift it any higher or risk losing stability while turning. In order to progress the pallet, pull the handle behind you; do not push it. There will be a large amount of momentum present. Refrain from quick or sharp turns and you should not stop too abruptly. Gently bring the pallet to a halt wherever you would like to park it. Squeeze the lever inside the grip end to restore the forks to the floor. Extract the forks from the pallet and return the pallet lift to its designated parking spot.